



Ordering Information

Catalog No.	Finishes	Mounting	Lamps
9220WH 9220BK	Matte White Matte Black	All Lytespan Track Systems	A19, R20, PAR16 75W Max PAR20 50W Max

Features

- Lytespan attachment fitting:** Die-cast zinc alloy.
- Housing:** .40" aluminum
- Step baffle:** Compression-molded high heat phenolic with stepped conical surface for low brightness. Integral black finish.
- Lever:** Locks attachment fitting electrically and mechanically anywhere along the track.
- Movable brass Contact:** Extends for connection to 2nd circuit in Advent Lytespan Track.
- Swivel:** Die-cast zinc alloy. 350° horizontal adjustment.
- Pivot mounting:** Tensioned with built-in stop, provides 90° vertical adjustment.

Electrical

Porcelain socket, medium base, nickel plated screw shell. No. 18 braided SF-1 leads.

Finish

All painted finishes baked enamel.

Labels

UL, I.B.E.W.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

Lightolier a Genlyte company

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2006 Genlyte Group LLC • A1006

www.lightolier.com

LIGHTOLIER®